

Product description

MASTERS ONE is a oils and oleines based sealant paste with inert fillers

Property

- · ready to use
- not corrosive
- paintable
- solvents free
- suitable for internal and external joints
- great workability

Application areas

Suitable for the sealing of:

- · glass and wood window frames
- wood and iron
- iron and glass
- anti-vibration and anti-noise joints filler

Preparation and use

Conditions of use: use at a temperature between +5°C and +50°C. It is advised to completely harden the product before painting.

Don't apply the product if its raining Protect from water for at least 72 hours

Surface requirements: the surface should be dry, free of dust, oils, detergents and greases, once the surface has been cleaned, wait no more than 20 minutes for laying the product.

Minimum joint size: 10x10 mm Maximum joint size: 20x15 mm

Tools for use: spatula or curved knife

Tools cleaning: clean them with water and soap

Spots and residues: remove non-crosslinked parts with water, hardened parts can only be removed mechanically.

Package

loaf 1 kg, box 20 pc loaf 5 kg, box 4 pc

Colours



Storage

Keep in its original packaging in a dry place, protected from direct light, and with temperature between + 5°C and + 25°C.

Security measures

Avoid contact with mucous membranes and skin
Use gloves to avoid irritation, especially in susceptible persons
In case of contact with eyes, rinse with large amounts of water consult a doctor.

Avoid to release the packages to the environment

MASTERS ONE - Product data		
General characteristics	unit	Value
t		
Base		Vegetal Oil
Appearance		Paste
Density	[g/cm ³]	2,10
Operating Temperature	[°C]	-20 / +80
Application Temperature	[°C]	+5 / +50

These figures are only intended as a guide and should not be used in preparing specifications.

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

The management system has been certified according to DIN EN ISO 9001 and DIN EN ISO 14001

For technical, quality, or product safety questions, please contact:

MASTICI VOTTERO s.n.c.

10040 La Cassa (TO) - via Torino 44

info@masticivottero.com

www.masticivottero.com